


Premium Horizontal Refrigeration LED Strip

Improve your refrigerated case display lighting with the Premium Refrigeration LED Strip. This strip is designed to fit perfectly in both canopy and shelf light applications, with a wide variety of mounting option. Improve the look of your displayed product and improve your customer experience with premium colours using high CRI and High R9 colour rendering technology.




FEATURES

- Canopy model with integrated optical lens, provides the optimal light spread.
- Aluminum design provides optimal heat dissipation for long life and reliability.
- Shatterproof polycarbonate lens.
- Life span of more than 50,000 hours.
- Operates on remote driver (AC120-277v)
- Available in a variety of lengths.
- Available in Canopy and Shelf models.
- Available in 2700K to 5700K , Hi-Spectrum and CRI>90 and R9>70
- Saves up to 80% energy consumption compared to traditional lighting.

Product Parameters

	MODEL	WATTS	INPUT VOLTAGE	LUMINOUS FLUX	CCT	CRI	BEAM ANGLE	WARRANTY	WORKING TEMP	MATERIAL
SHELF	GWL-AL-S-0550-032-XXK-D-C95	3.2	Driver AC100-277V	> 419 lm	2700K	≥90	105°	5 years	-30° - 45° C	Aluminium & PC
	GWL-AL-S-0850-048-XXK-D-C95	4.8	LED Strip DC 24V	> 624 lm	3000K					
	GWL-AL-S-1200-064-XXK-D-C95	6.4		> 835 lm	4000K					
CANOPY	GWL-AL-C-0550-096-XXK-D-C95	9.6	Driver AC100-277V	> 1050 lm	2700K	≥90	75°	5 years	-30° - 45° C	Aluminium & PC
	GWL-AL-C-0850-144-XXK-D-C95	14.4	LED Strip DC 24V	> 1550 lm	3000K					
	GWL-AL-C-1200-200-XXK-D-C95	20.0		> 2300 lm	4000K					

Product Dimensions




Length	2FT	3FT	4FT
A (MM)	550	850	1200
B (MM)	15	15	15
C (MM)	19.4	19.4	19.4

Product Order Code

GWL	PF	XX	PF	XXK	D	C95
GWL	PRODUCT SERIES AL-S- Aluminum Shelf AL-C - Aluminium Canopy	SIZE XXXX Millimeters	WATTAGE 032 - 3.2 watt 048 - 4.8 watt 064 - 6.4 watt 096 - 9.6 watt 144 - 14.4 watt 200 - 20.0 watt	CCT 27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K HSP - Hi Spectrum	D - DOUBLE END POWER	C93- CRI >95



Product Accessories



MAGNET MOUNTING CLIP
GWL-ALU-MAG



STAINLESS STEEL
MOUNTING CLIP
GWL-ALU-MC



LED 4M CONNECTOR WIRE
GWL-DC-G4



80W, 100W, 150W LED DRIVER
GWL -FSL-LD3-XXX24V

